



SIMPSON[®]
TECHNOLOGIES

Model #MC-100
Simpson Multi-Cooler[®]



Description

The [Simpson Multi-Cooler](#) is the world's most popular sand cooling and pre-conditioning equipment. The Multi-Cooler is available in sizes to match operations ranging from small jobbing foundries to large-scale automated facilities.

Features & Benefits

- Crib design insures "minimal sand" in the air plenum.
- Exterior of the crib and interior of the air plenum are fabricated from steel. The floor of the Multi-Cooler is constructed of abrasion resistant replaceable ceramic tiles.
- Eight plows faced with wear resistant carbide.
- An electromechanically actuated discharge door which maintains sand discharge rate equal to charge rate.
- Automatic in-line moisture control.
- Dual drive, consisting of two speed reducers. The reducers are coupled to the vertical shafts with pin-type couplings, replaceable pins and bushings.
- A pneumatic disc clutch permits starting and stopping with a full load of sand.
- Centralized lubrication system.
- Dusthood, cyclone and PLC based controls.
- Discharge sand temperature at or below 120°F.
- Reduced variation in key sand properties.
- Reduced sand defects and scrap caused by hot sand.
- Reduction in bentonite consumption (w/optional BAS).



SIMPSON[®]
TECHNOLOGIES

Model #MC-100
Simpson Multi-Cooler[®]

Technical Data

Specification	100MC
Capacity (US) (Tons/hr)	100
Cooler Length	13'-8"
Overall Width	8'-2 1/8
Overall Height	11'-3"
Cooler Width	8'-1 1/2 "
Clearance Under Discharge Door	39"
Typical Fan Length	48 1/2 "
Typical Overall Length	20'-8 1/2 "
Drive Motor hp/rpm	50/1,800
Supply Fan hp/rpm/cfm	80/1,800/10,600
Exhaust cfm	16,000
Shipping Weight (lbs)	16,000